

WOK LINE

This exceptional wok appliance offers 12 power levels and has a Ceran wok cuvette with a diameter of 300 mm. It is especially energy efficient and is operated using the new "Tip and Turn" control knob. Further highlights are the integrated timer function, the high operational reliability and the transfer of power with no pauses for measurement.







	INSTINCT WOK 3.5	INSTINCT WOK 5	INSTINCT WOK 5
--	-------------------------	----------------	-----------------------

Number of heating zones	1	1	1
Ceran glass surface B x D (mm)	Ø 300 Wok Ceran bowl	Ø 300 mm Wok Ceran bowl	Ø 300 mm Wok Ceran bowl
Inductor diameter (mm)	Ø inductor coil 270	Ø inductor coil 270	Ø inductor coil 270
Power levels	12	12	12
Housing	Stainless steel	Stainless steel	Stainless steel
Electrical supply	240V/50-60 Hz/1 phase	240V/50-60 Hz/3 phase	240V/50-60 Hz/3 phase
Dimensions (W x D x H, mm)	356 x 473 x 200	356 x 473 x 200	356 x 473 x 200
Power output (W)	3500	5000	8000



INDUCTION GRILL

This ultra-modern griddle appliance provides a temperature setting range of 50 - 230°C, has a very functional non-stick frying surface and a practical timer function. It is exceptionally energy efficient and its extremely short heating time and the absolutely uniform distribution of heat are truly impressive.







	INSTINCT GRIDDLE 3.5	INSTINCT GRIDDLE 5	INSTINCT GRIDDLE 10
Number zones	1	1	2
Griddle B x D (mm)	493 x 352	493 x 352	618 x 577
Temperature setting (°C)	50 to 230	50 to 230	50 to 230
Housing	Stainless steel	Stainless steel	Stainless steel
Electrical supply	240V/50-60 Hz/1 phase	240V/50-60 Hz/3 phase	240V/50-60 Hz/3 phase
Dimensions (W x D x H, mm)	530 x 492 x 197	530 x 492 x 197	356 x 473 x 200
Power output (W)	3500	5000	2 x 1250 - 5000
l de la companya de			(can be reduced individually)



INDUCTION HOB

This appliance with one cooking zone has 12 power levels with a holding function of 25 to 100°C and a timer function. It is especially energy efficient and is operated using the new "Tip and Turn" control knob. The appliance is convenient and operationally reliable and its very short heating times are impressive.







INCTINCT HOD E

	IN21ING1 HOR 3.5	IN21INCLHOR 2	IN21INCL HOR IO
Number of heating zones	T	1	2
Ceran glass surface B x D (mm)	372 x 349	372 x 349	372 x 609
Inductor diameter (mm)	Ø 220	Ø 220	Ø 220
Power levels	12	12	2 x 12
Warm-holding function (°C)	25 to 100	25 to 100	2 x 25 to 100
Housing	Stainless steel	Stainless steel	Stainless steel
Electrical supply	240V/50-60 Hz/1 phase	240V/50-60 Hz/3 phase	240V/50-60 Hz/3 phase
Dimensions (W x D x H) mm	356 x 460 x 140	356 x 460 x 140	356 x 721 x 140
Power output (W)	3500	5000	2 x 1250 - 5000

INCTINCT HOD 2 F

(Max. 5000, can be reduced individually)

INCTINCT HOD 10